













## GIXXER SF 250/GIXXER 250 Series Specifications

Engine	
Engine Type:	4-Cycle, 1-Cylinder, Oil-Cooled
Valve System:	SOHC
Displacement:	249 cm²
Bore x Stroke:	76 mm x 54.9 mm
Max Power:	26.5ps@9300rpm
Max Torque:	22.2Nm@7300rpm
Fuel System:	Fuel Injection
Starter System:	Electric
Transmission Type:	6 Speed, MT

Dimensions and Weight	
Wheels:	Cast
Overall Length:	2010 mm
Overall Width (GIXXER SF 250):	740 mm
Overall Width (GIXXER 250):	805 mm
Overall Height:	1035 mm
Wheel Base (GIXXER SF 250):	1345 mm
Wheel Base (GIXXER 250):	1340 mm
Ground Clearance:	165 mm
Kerb Mass (GIXXER SF 250):	161 kg
Kerb Mass (GIXXER 250):	156 kg
Seat Height:	800 mm
Eugl Tanks	121

Susp	pension
Front: Rear:	Telescopic Swing Arm
Tyre	Size
Front:	110/70R17M/C 54S
Rear:	150/60R17M/C 66S
Brak	е
Front:	Disc
Rear:	Disc

Electrical	
Battery:	Maintenance free, 12V 6Ah
Headlight:	LED
Tail Light:	LED





Regd. Office, Sales & Marketing Office: 2nd Floor, Plot No. 1, Nelson Mandela Road, Vasant Kunj, New Delhi - 110 070, Fax: 011-4607 5418.

😨 Ride safe. Wear a helmet. | Prices of the vehicles are available on our website. | Visit us an xwwaszukimotorcycloscia 🧗 Suzuki2whoelers. 🌃 smittXXR 7mini Suzuki2whoelers. 📆 Suzuki2whoelers. 🔞 Suzuki2whoelers.

Specifications, appearances, equipments, colours, materials and other items of Suzuki product shown in this leaflet are subject to change by the manufacturers at any time without notice and they may vary depending upon local conditions and requirements. Please visit your local dealer for details of any changes. Actual body colour may differ from the colours in this leaflet. \*ABS is not designed to shorten the braking distance. ABS cannot prevent wheel skidding caused by braking while cornering. Please ride carefully and do not overly rely on ABS.